



Recycled
Materials
Resource
Center



THE UNIVERSITY
of
WISCONSIN
MADISON

Project Principle Investigators

Tuncer Edil, Ph.D.
Tel: (608) 262-3225
Email: tbedil@wisc.edu
Haifang Wen, Ph.D.
Tel: (509) 335-2513
Email: haifang_wen@wsu.edu
Department of Civil Engineering
University of Wisconsin-Madison
Madison, WI 53706

RMRC

University of Wisconsin-Madison
Engineering Centers Building
1550 Engineering Drive
Madison, WI 53706
Tel: (608) 890-4966
Email: angela.pakes@wisc.edu
<http://www.rmrc.wisc.edu>

Research Project 48

Utilization of Cementitious High Carbon Fly Ash in CIR

Project Objectives

- Evaluation of the performance of cementitious high carbon fly ash (CHCFA) stabilized recycled asphalt pavement as a base course material.
- Determination of how CHCFA stabilized base course compares to conventional base courses like crushed virgin aggregate and untreated recycled asphalt pavement.

Project Summary

Due to the increasingly stringent environmental policy stipulated by the Environmental Protection Agency (EPA) and/or local authority, the power generation industry must take measures to reduce the emission of nitrogen oxides (NO_x), sulfur oxides (SO_x), and Mercury (Hg). Low-NO_x burners reduced emissions by changing the combustion characteristics of coal boilers, but increased the amount of residual unburned carbon in ash. Additionally, activated carbon is injected to reduce mercury emission, which also increases the carbon level in fly ash. In 2002, approximately 76.5 million tons of fly ash was produced in the U.S. and about 49.8 million tons of that was placed in landfills, resulting in significant land purchase and energy costs, and potential environmental issues. Simultaneously, most of highways in the United States were built in 1950s and 1960's and have deteriorated significantly to date. More than 96 percent of the current highways consist of asphalt pavements. Quarrying virgin aggregates for highway construction also results in environmental problems and energy consumption. An

alternative to quarrying virgin materials is in-place recycling of asphalt pavement. However, there are concerns on the load-carrying capacity and deformability of a base layer made of RPM. Cementitious high carbon fly ash (CHCFA) has self-hardening properties in the presence of moisture, like the property of Class C fly ash. However, the high carbon content in CHCFA eliminates CHCFA from being used in concrete, because the carbon in fly ash absorbs the air entraining admixture in concrete, affecting the durability of concrete. Unlike concrete which 3 needs air void (generally 6%), air void is not desired in a base course of an asphalt pavement. A base course with maximum density and minimal air void lasts longer than a loose base course. Therefore, the high carbon content in CHCFA presumably does not affect the performance of a base course. Stabilization of RPM with CHCFA could create a strong base course, which improves the long-term performance of asphalt pavement and beneficially utilizes the high carbon fly ash, which would otherwise be landfilled. Our goal was to test this hypothesis.

Project Partners

Minnesota Department of Transportation, Bloom Companies, LLC

End Products

The laboratory and field tests showed that fly ash stabilized RPM had higher modulus than crushed aggregate and RPM did. Based on the MEPDG performance prediction, the service life of the cell containing fly ash stabilized RPM, is 23.5 years, which is about twice the service life (11 years) of the cell with RPM base, and about three times the service life (7.5 years) of the cell with crushed aggregate base. The life cycle analysis indicated that the usage of the fly ash stabilized RPM as the base can significantly reduce the life cycle cost, energy consumption, and greenhouse gas emission.

Further Information

The Recycled Materials Resource Center (RMRC) is a national center that promotes the appropriate use of recycled materials in the highway environment. It focuses on the long-term performance and environmental implications of using recycled materials